


REQUIRED SAFETY EQUIPMENT



SAFETY FIRST

If you are collecting the equipment for someone else please make sure this sheet is given to the equipment user to read. This sheet should be given to the site supervisor if the equipment is being hired for commercial use so that the information is available to all users.

Before starting any job, be sure to spend a few minutes planning and understanding the hazards and risks of the job. Do this by:

- Thinking about and observing your surroundings
- Running through the steps of the job in your mind
- Identifying the hazards, how you can get hurt and how you'll prevent it
- Knowing what plant and equipment you need
- Only starting when you can do the job safely
- Ensuring you are trained or experienced for the task
- Communicating with everyone involved

Points to consider when planning a task. Can you:

- Come into contact with an energy source (e.g. heat, electricity, substance under pressure) or hazardous materials
- Be struck-by or against anything?
- Be caught-in, on or between anything?
- Slip, trip or fall on the same or too a lower level
- Strain or sprain a muscle?
- Cause damage to plant equipment or property?
- Spill or pollute something?

Water Cart – Skid Mount

Instructions for Use



Pre-Start Checks and Safety

- If loading onto a vehicle the tank needs to be empty
- Ensure the vehicle carrying the water cart is capable of carrying the full weight and there is no axle overloading
- Water tank is tied down securely to prevent any movement
- Ensure 3 points of contact whenever accessing the tank or accessories whilst mounted on the truck
- Fill with water only from an approved source
- Do not use this tank for drinking water or any human consumption

When Operating

- Ensure any bystanders are aware of your work
- It is not recommended to use the remote while driving
- It is best not to run out of water, if the water runs out, stop the engine immediately
- If filling with the pump from a water source, turn ball valve off on the tank, remove the camlock fitting, swap the hose from the tank to the other side, attach the 6m suction hose to the pump, turn ball valve on and operate pump. When finished, turn ball valve off, swap tank hose back, attach camlock fitting and turn the ball valve back on. Secure the suction hose.
- Details

Starting Procedure

- Turn power on
- If cold starting, start machine using the choke. You will need to stand beside the engine for this
- The engine and spray bars can be started and stopped at any time using the supplied remote
- If using the wash down hose be sure to turn off the spray nozzle

Stopping and After Use

- Turn engine off and turn off power
- If removing from the vehicle ensure the tank is empty and the engine has cooled down.
- Do not tip the unit off a tip truck, always use the lift points or the fork pockets
- Stow the remote in the manual holder